



Art.No. 103800

Voltage tester "Basic +"



Art.No.	103800
EAN	4011923172657
Type of test	2-pole
Voltage indication	LED
Voltage measuring range	6 - 400
TL	120 mm
Internal base load	Yes
Load switchable	No
Indication of direction of field rotation	No
Single pole phase indication	No
Contact less voltage detection	No
Voltage measurement range	6 - 400 V
Data hold	No
Background lighting LC-indication	No
Test prod protection	Yes
Measuring point lightning	No
Current supply	Battery
Measuring circuit category	CAT III
VPE	1

The two-pole voltage tester reliably indicates direct and alternating voltages within a range of 6 to 400 V in 7 intervals per LED (6, 12, 24, 50, 120, 230 and 400). The electronics also enable the determination of polarity and the phase to protective conductor. The "Basic +" is characterised by a userfriendly construction and robust housing that ensures long operational life. The rubberised handles offer non-slip hold. The "Basic +" operates without batteries. It takes its operating voltage from the test object.

Functions and benefits

- User-friendly and robust
- Voltage range up to 400 V AC/DC
- Phase search to protective conductor

Technical data „Basic +“

Display: Optical, 8 LEDs

Over-voltage category: CAT III 400 V

Dimensions: 120 x 60 x 30 mm

Weight: 100 g

Colour: Red/black

Accessories (optional): Carry bag

Voltage range: 6 - 400 V AC/DC

Housing: High quality plastic with rubberised handle area



Distributed by:

HAUPA GmbH & Co. KG, Königstr. 165-169, 42853 Remscheid, Germany, Tel. +49 (0)2191 8418-0

HAUPA, Bayernstr. 39, 5071 Wals-Siezenheim, Austria, Tel. +43 (0)662 854717

HAUPA Ibérica S. L., c/ Muralla de Sant Llorenç, 37 2ªA, 08302 Mataró (Barcelona), Spain, Tel. +34 902 313135

HAUPA Polska Sp. z o.o., ul. Norwida 11, 55-100 Trzebnica, Poland, Tel. +48 (0)71 3874813

HAUPA-RU Ltd, ul. Industrialnaya, 9/1, 180021 Pskov, Russia, Tel. +7 (8112) 292878

iCON by HAUPA d.o.o., Mise Dimitrijevic 44, 21000 Novi Sad, Serbia, Tel. +38 121 300 29 37